A Parallel Algorithm for Eliminating Cycles in Undirected Graphs

Philip Klein*
Computer Science Department
Brown University
Providence, RI

Clifford Stein †
Laboratory for Computer Science
MIT
Cambridge, MA

Abstract

We give an efficient parallel algorithm for finding a maximal set of edge-disjoint cycles in an undirected graph. The algorithm can be generalized to handle a weighted version of the problem.

Keywords: parallel algorithms, undirected graphs, cycles, Euler tour.

1 Introduction

The first problem in graph theory was posed by Euler when he asked the now famous *Königsberg Bridge Problem.* This problem can be phrased in graph-theoretic terms as:

Given an undirected graph G, find a cycle that covers every edge in the graph exactly once.

A cycle of this form is called an *Eulerian cycle* and a graph that contains such a cycle is called an *Eulerian graph.* Euler showed that a graph has an Eulerian cycle if and only if the graph is connected and every vertex in the graph has even degree. Moreover, there is a linear time sequential algorithm which, given an Eulerian graph, finds an Eulerian cycle. Awerbach, Israeli, and Shiloach [2] have given a parallel

*Research partially supported by ONR grant N00014-88-K-0243 and DARPA grant N00039-88-C0113 at Harvard University

†Research supported by a graduate fellowship from GE. Additional support provided by Air Force Contract AFOSR-86-0078, and by an NSF PYI awarded to David Shmoys, with matching funds from IBM, Sun Microsystems, and UPS.

algorithm to solve this problem in $O(\log n)$ time using $n + m$ processors, for graphs with n nodes and m edges.

In this paper, we consider the closely related problem of finding a maximal set of edge-disjoint cycles in a graph. Given a graph, we would like to identify a collection of edge-disjoint cycles whose removal renders the graph acyclic. We give a parallel algorithm that solves this problem for n-node, m-edge undirected graphs in $O(\log n)$ time on $n+m$ processors on a concurrent-read concurrent-write parallel random access machine (CRCW PRAM) [10]. In fact, using randomization, our algorithm can be implemented to run in $O(\log n)$ time using only $(n + m)/\log n$ processors. Since the problem requires $\Omega(n + m)$ operations in the worst case, the resulting randomized algorithm is optimal in its use of parallelism.

The maximal edge-disjoint cycles problem is inspired by a problem that arises in finding a minimum-cost circulation in a network, namely, finding a maximal set of weighted cycles in a positively-weighted directed graph. In this case, the weight of an edge represents the capacity of that edge, and the weight of a cycle represents the flow on that cycle. A maximal set of weighted cycles corresponds directly to a set of capacitated cycles such that, after flow is pushed around these cycles, the graph of edges which still have positive capacity is acyclic. Goldberg and Tarjan [9] solve the minimum-cost circulation problem by repeatedly finding a maximal set of weighted cycles; they show how to solve the latter problem sequentially in $O(m \log n)$ time.

While we cannot solve this problem efficiently, we can solve the undirected version of it by generalizing our algorithm for eliminating cycles in undirected graphs to handle integer-weighted undirected graphs as well. We think of the edge weights as edge multiplicities and find a set of cycles with multiplicities, whose removal renders the graph acyclic. The algorithm takes $O(\log n \log U)$ time on $n + m$ processors of a CRCW PRAM, where U is the largest weight in the graph.

In view of the application to minimum-cost circulation, it is an important open problem to determine whether there is an efficient parallel algorithm for eliminating cycles in a weighted directed graph. At present, the most efficient parallel algorithm for this problem uses a reduction to weighted non-bipartite matching, which takes $O(\log^2 n)$ time on $Mn^{3.5}m$ processors, and uses randomization[12] .

2 Preliminaries

Let $G = (V, E)$ be an n-node undirected graph with node set V and edge set $E = \{e_1, \ldots, e_m\}$. Let $\{0,1\}^E$ denote the m-dimensional vector space over $GF(2)$. Each subgraph H of G corresponds to a vector $\mu(H) = (\mu_1, \ldots, \mu_m)$, where $\mu_i = 1$ if edge e_i appears in H, and $\mu_i = 0$ otherwise. An *even-degree subgraph* of G is a subgraph in which every node has even degree. Every connected component of an even-degree subgraph is Eulerian; hence, the edges of such a subgraph can be decomposed into cycles. Furthermore, it is well-known (and easy to see) that the vectors corresponding to even-degree subgraphs of G form a vector subspace of $\{0,1\}^E$, called the *cycle space* of G and denoted $\mathcal{C}(G)$. That is, for two even-degree subgraphs H_1 and H_2 of G, the elementwise mod 2 sum of the vectors $\mu(H_1)$ and $\mu(H_2)$ is again a vector $\mu(H)$ corresponding to an even-degree subgraph H.

Let F be a spanning forest of G. Let $\hat{F}$ be a rooted version of F; that is, $\hat{F}$ is obtained from F by choosing a root within each tree of F. For each node v, there is a unique simple path $P(v)$ from v to the root of the tree containing v. For two nodes v and w belonging to the same tree, the *lowest common ancestor* of v and w, denoted $lca(v, w)$, is the first node common to $P(v)$ and $P(w)$.

An edge $e = (v, w)$ of G not appearing in F is called a *cycle-edge* (with respect to F) because $F \cup \{e\}$ contains a unique simple cycle, denoted $C(e)$. In particular, the cycle $C(e)$ consists of e, together with the paths from v and w to their lowest common ancestor in $\hat{F}$. Using the $GF(2)$ vector notation, we can write the cycle as

$$\mu(C(e)) = \mu(e) + \mu(P(v)) + \mu(P(w)). \tag{1}$$

because the portions of $P(v)$ and $P(w)$ from $lca(v, w)$ to the root coincide and cancel each other. It is well known that this collection of cycle vectors $\{\mu(C(e)) | e \notin F\}$ forms a *cycle basis*, i.e. a set of linearly independent vectors which span the cycle space. [3] We will refer to this particular basis as $\mathcal{B}$.

3 The Algorithm

Consider the even-degree subgraph H obtained by adding together mod 2 all the cycles $C(e) \in \mathcal{B}$. That is, H is defined by

$$\mu(H) = \sum_{e \notin F} \mu(C(e)) \tag{2}$$

where the sum is elementwise mod 2. Since every edge e not in F occurs exactly once in the sum, e is in the subgraph H. Thus H contains all non-forest edges and possibly some forest edges. However, all edges not in H must be in F, so the set of edges not in H form an acyclic graph. It follows that when the edges of H are removed from G, the remaining edges form an acyclic subgraph. Moreover, H can be decomposed into edge-disjoint cycles. These observations suggest the following algorithm for finding a maximal set of edge-disjoint cycles in G:

Step 1: Choose a rooted spanning forest $\hat{F}$ of G.

Step 2: Determine the subgraph H of G by (2).

Step 3: Decompose H into edge-disjoint cycles.

Step 1 can be implemented in $O(\log n)$ time using $n+m$ processors by the spanning tree algorithm of Shiloach and Vishkin [13], or using $(n+m)/\log n$ time by the randomized algorithm of Gazit [7]. Step 3 can be implemented in $O(\log n)$ time using $(n+m)/\log n$ processors by the list-ranking algorithm of Cole and Vishkin [4] or that of Anderson and Miller [1]. A naive implementation of step 2 consists of summing at most $m-n+1$ vectors of length m. This approach takes $O(\log n)$ time but requires about m^2 processors. We describe an approach that takes advantage of the structure of the problem to achieve $O(\log n)$ time using only $(n+m)/\log n$ processors.

Every edge of G that is not in the forest F is automatically in the subgraph H. Thus, we need only determine which edges of F are contained in H. We use (1) to rewrite (2) as

$$\mu(H) = \sum_{e=(v,w)\notin F} [\mu(e) + \mu(P(v)) + \mu(P(w))] \tag{3}$$

Let (x, y) be an edge of $\hat{F}$, with y the parent of x. Equation (3) implies that (x, y) is in H if and only if the mod 2 sum

$$\sum_{v \text{a descendant of } x} |\{(v,w)\ :\ (v,w) \notin F\}| \tag{4}$$

is 1. In order to compute H, therefore, it suffices to compute the sum (4) for each node x of G.

Let A be the rooted forest obtained from $\hat{F}$ by adding two new nodes a_i and b_i and two new edges (a_i, x) and (b_i, y) for each edge $e_i = (x, y) \in G - F$. That is, A is obtained from G by splitting in two each edge not in $\hat{F}$, as illustrated in Figure 1. Observe that the number of nodes in A, including new nodes, is at most $n + 2m$.

In the resulting rooted forest A, each of the new nodes a_i and b_i is a leaf of A. It is easy to see that the number of new nodes connected to an old node v is $|\{(v,w)\ :\ (v,w) \notin F\}|$. Hence for each node x of G, the number of descendants of x in A that are new nodes gives the value of (4). Using Tree Tour [14], we can compute these values for all old nodes x of G simultaneously, in $O(\log n)$ time using $(n+m)/\log n$ processors.

Thus we have proved the following theorem: